VERDERFLEX VP2-HT MA

Dosing pump system for pools and water treatment

Description

Peristaltic digital, proportional dosing pump for dosing chemicals according to input from external mA signal. Wall and foot mounted pumps available. Protection class IP 55. This dosing pump system has a longer engine life and better performance under pressure because of a bearing on the rollers holder.



Features

- Built-in controller dosing according to mA
- → Overdosing time alarm
- → Start time delay setting
- Status and programming led alarm
- → STAND-BY function to stop dosing
- Priming button for quick installation
- → Default parameter restore option
- → Hose break sensor/alarm
- → Level probe sensor input for checking product levels
- → On/off switch
- → Schuko plug

Function modes

- → Manual: constant
- On/Off: cyclic dosing with programmable delay
- mA; proportional dosing according to mA received, proportional dosing freely programmable

Display

- → Backlit LCD display, 16 x 2 characters
- → 4 Languages
- → Display of flow rate
- Password protected

Options

- Personalized front
- Three rollers for more accurate dosing
- → Temperature sensor input
- Flow sensor input for dosing according to flow
- → Alarm relay output

Technical data

| Pump body | PP reinforced with 30% fiberglass | Rolls | Delrin | |
|-----------|-----------------------------------|-------------------|--------------------------|--|
| Tube | Santoprene | Power | 90 - 250 VAC, 50 – 60 Hz | |
| Fittings | PP ring nuts 4x6 mm tube | mA signal fitting | HTP | |

| Model | Max. l/h | Max cc/min | Pressure (bar) | Tube ø mm | Power cons. (Watt) | rpm | Weight (kg) |
|--------|-------------|---------------|-------------------|--------------|-----------------------|-----|----------------|
| 03-01* | 3.0 | 50 | 1 | 5.8 x 9.3 | 20 | 20 | 0.9 |
| 06-01* | 6.0 | 100 | 1 | 5.8 x 9.3 | 20 | 48 | 0.9 |
| 12-01* | 12.0 | 200 | 1 | 5.8 x 9.3 | 20 | 104 | 0.9 |
| 20-01* | 20.0 | 333.3 | 1 | 5.8 x 9.3 | 20 | 150 | 0.9 |
| 02-04* | 2.0 | 33.3 | 4 | 4.8 x 9.6 | 20 | 20 | 0.9 |
| 05-04* | 5.0 | 83.3 | 4 | 4.8 x 9.6 | 20 | 48 | 0.9 |

^{* 20%} flow rate decreasing on 3 rolls version. Please consult supplier for effects 3 rollers

VERDERFLEX VP2-HT MA

Dosing pump system for pools and water treatment

Dimensions

(in mm)





Standard intallation kit

| PP-VL-VT 1/2" | PP-VL-VT 1/2" Foot filter | Delivery tube | Suction tube | |
|---------------------|---------------------------|---------------|--------------|--|
| Injection lip valve | with lip valve | 2 m PE 4x6 | 2 m PVC 4x6 | |
| | | | | |





